

SLIMLINE LED

P A N E L



SQUARE SPECIFICATIONS

Wattages	12W, 18W, 24W
Input Voltage	AC100-277V*
Luminous Efficiency	80LM/W
Color Temperature	3000K to 5000K
Dimmable	0-10V
Beam Angle	180°
Working Temperature	-4°F to 122°F

**Wide range voltage and 120V available.*

ROUND SPECIFICATIONS

Wattages	6W, 12W, 18W, 24W
Input Voltage	AC100-277V*
Luminous Efficiency	80LM/W
Color Temperature	3000K to 5000K
Dimmable	0-10V
Beam Angle	180°
Working Temperature	-4°F to 122°F

**Only 120V available for 6W.*

LUMENS

100-277V Model

12W:	162x162x15mm	1000lm
18W:	214x214x15mm	1500lm
24W:	289x289x15mm	2000lm

120V Model

12W:	162x162x15mm	960lm
18W:	214x214x15mm	1440lm
24W:	289x289x15mm	1920lm

LUMENS

100-277V Model

12W:	180x13mm	1000lm
18W:	225x13mm	1500lm
24W:	300x13mm	2000lm

120V Model

6W:	135x13mm	360lm
12W:	180x13mm	960lm
18W:	225x13mm	1440lm
24W:	300x13mm	1920lm

MOUNTING

The Slimline LED Panel can be easily mounted via rotatable installation into a junction box. In the diagram, the junction box is recessed into a surface with a can.



Silver



Matte Black



White



Bronze



STYLE

The Slimline LED panel comes in two shapes to suit your design needs. Choose either round or square. Both styles come with multiple housing colors that can attach to the light with a simple magnet.

SIZE

The Slimline LED panel provides a low profile that makes it a lightweight option for any ceiling. The square panel's thickness measures only 15mm in thickness, while the round option is 13mm no matter what the size.

